ultraTile
engineered with NOVIK™

A BEAUTIFUL TILED FINISH,

LIGHT ENOUGH TO SIT ON EXISTING WINDOW FRAMES

The UltraTile polymer roofing system is part of the UltraRoof system.

The UltraTile polymer roofing system not only replicates the natural look of slate tiles but is easier to install and less expensive without incurring the extra structural cost needed to accomodate conventional slate roofing. The UltraTile polymer roofing system is also designed to outperform and be more cost-effective than any other synthetic slate tile replica system on the market.

COLOURS AVAILABLE

Carbon grey

Harvest Brown

Terra Brick

ENHANCED PERFORMANCE FEATURES

No individual tile overlapping necessary.

Innovative screw locators that facilitate the installation by precisely indicating screw locations.

Centered screw hole to secure panel.

Special temperature lines molded to ensure precise installation under 40°F.

A structural system was added on the back of the panel for protection and stability, making the UltraTile roof tile resistant enough to be stepped and walked on. Allows air to circulate underneath the panel.

Overall dimensions: 135,3 cm x 57,15 cm x 1,9 cm
8 panels per box: approximately 4,65 m² / 0,58 m² per panel

Vertical stoppers   **Lateral stoppers**

A Stoppers (on the back of the panel) ensure correct positioning of the panel and enable the necessary expansion and contraction for installation above 5°C.

B Guidelines to validate appropriate assembly (locking or insertion) for installation above 5°C.

Each UltraTile panel is held securely in place with extra long tabs that engage easily for faster and easier installation.

FEATURES AND BENEFITS

- Extreme temperature variation resistance
- Resistance to warping, expansion, contraction and cracking
- Wind and hail impact (Class 4) resistance
- Resistance to discolouration (U.V. rays)
- Fire resistance to ASTM standards
- Virtually maintenance free
- Colour-through process
- Lightweight material, fast and easy to install
- Authentic slate tile texture
- Features that simplify installation
- Certified testing by independent laboratories

ACCESSORIES AVAILABLE

Ridge Cap

Overall dimensions:
27.9 cm x 9.5 cm x 24.2 cm

UltraTile Starter Strip

Overall dimensions: 121 cm x 5.6 cm

www.ultraframe.co.uk

ultraTile
engineered with NOVIK